

Tabla de Rendimientos por Diámetro de Alambre

Abertura	Ø Alambre	Área Útil	Abertura	Ø Alambre	Área Útil
3/16"	2.5 MM	42,99%	1"	10 MM	52,91%
4.76 MM	2.0 MM	49,58%	25.40 MM	8 MM	58,04%
1/4"	3.5 MM	41,56%	1 1/4"	10 MM	59,19%
6.35 MM	3.0 MM	46,12%	31.75 MM	8 MM	63,99%
5/16"	4.0 MM	44,22%	1 1/2"	12 MM	56,25%
7.94 MM	3.5 MM	48,17%	38.10 MM	10 MM	64,01%
3/8"	4.5 MM	46,11%		8 MM	68,48%
9.53 MM	4.0 MM	49,58%	1 3/4"	12 MM	60,49%
	3.5 MM	52,68%	44.45 MM	10 MM	67,83%
7/16"				8 MM	71,09%
11.11 MM	4.0 MM	54,06%	2"	12 MM	64,00%
			50.8 MM	10 MM	70,95%
1/2"	5.0 MM	51,48%		8 MM	74,79%
12.70 MM	4.5 MM	54,52%	2 1/4"	12 MM	66,94%
5/8"	5.0 MM	57,82%	57.15 MM	10 MM	73,48%
15.87 MM	4.5 MM	60,70%	2 1/2"	12 MM	69,44%
3/4"	8.0 MM	49,82%	63.50 MM		
19.05 MM	6.0 MM	57,85%	2 3/4"	14 MM	68,92%
7/8"	8.0 MM	54,28%	69.85 MM	12 MM	71,60%
22.22 MM	6.0 MM	62,00%	3"	14 MM	70,93%
			76.20 MM	12 MM	73,47%